

RETRACTA[®] 
by macnaught



RETRACTA HOSE REELS
R3 SERIES



RETRACTA IN THE INDUSTRY

Retracta is the benchmark in industrial strength retractable hose reels. Over the decades the original Retractable poly reel has built an enviable reputation worldwide for performance and reliability. Through this, and with a long history of innovation and design, Macnaught has now developed an exciting new range of Retractable reels specifically designed and engineered for the most demanding industrial applications and environments.

Innovation has always been at the centre of the Macnaught success story and it's the platform for developing our expanded Retractable range.

At Macnaught we call it "Innovation by Design".

Because we know that innovation is the only way to stay ahead. This is what sets us apart from our competitors and gives our customers confidence backed by up to 10 year* mechanical warranty and guaranteed parts availability.

Retracta R3 RetractaFLEX Series

PREMIUM AIR & WATER HOSE REEL



Tangled hose lines will be a problem of the past. The NEW RetractaFLEX features an innovative hybrid polymer that allows for the ultimate in flexibility and kink resistance under pressure. Fitted with a bend restrictor at the hose end, the UV stabilised, abrasion-resistant outer layer provides maximum durability.

Great flexibility within temperature range

Kink-free under pressure

HI-VIS fluorescent colours for workplace safety

Memory free hose lays flat on the floor



Light weight and easy to handle

Unique patented RACR (on selected models)

Bend restrictor included*

AIR / WATER



Why choose this product?

The new RetractaFLEX hose reel comes standard with an innovative hybrid polymer hose allowing for ultimate flexibility and kink resistance under pressure.

Features & Benefits

- Innovative hybrid polymer hose – Ultimate flexibility
- High visibility Yellow, Orange colour hoses for visual identification & safety (Green for garden)
- Upgraded main spring made with TRC – Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR* – on selected models



Applications:
Suitable for use across all industries

Service Parts available when requested.

Standard	RY315B-01	RY320B-01	RO320B-01	RY420B-01	RO420B-01	RY325B-01
RACR®	X	RYC320B-01	ROC320B-01	RYC420B-01	ROC420B-01	X
Case Colour	Blue	Blue	Blue	Blue	Blue	Blue
Hose Size (ID)	10mm (3/8")	10mm (3/8")	10mm (3/8")	12mm (1/2")	12mm (1/2")	10mm (3/8")
Hose Length	15m	20m	20m	20m	20m	25m
Hose Color	Yellow	Yellow	Orange	Yellow	Orange	Yellow
Hose Material	RetractaFLEX Hybrid Polymer					
Working Pressure	300 psi	300 psi	300 psi	300 psi	300 psi	300 psi
Max Temperature	60°C (140°F)	60°C (140°F)	60°C (140°F)	60°C (140°F)	60°C (140°F)	60°C (140°F)
Reel Inlet	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)
Hose Outlet	1/4" BSP (M)	1/4" BSP (M)	1/4" BSP (M)	3/8" BSP (M)	3/8" BSP (M)	1/4" BSP (M)

Retracta R3 Series

COMPRESSED AIR




The Retracta R3 Premium series is the most robust and reliable hose & reel combination on the market. The highly durable Premium Reinforced PVC hose and industrial strength poly reel gives complete confidence in any demanding industrial compressed air application. The R3 Premium can be upgraded with the RACR system offering true control by allowing the user to set the speed of return to suit their individual requirements.

Unique patented RACR (on selected models)

Working pressure 275psi

Flexible & abrasive resistant hose cover

Available in 15m and 20m variants



Also available in Blue cases

Features & Benefits

- Highly durable Premium Reinforced PVC hose
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Why choose this product?


The robust Retracta R3 - AR series reels for compressed air all carry the Premium Reinforced PVC hose for maximum durability and high pressure rating.

Applications:

Suitable for use across all industries


Service Parts available when requested.

COMPRESSED AIR



Standard	AR320R-01	AR415R-01	AR420R-01
RACR®	ARC320R-01	ARC415R-01	ARC420R-01
Case Colour	Red	Red	Red
Hose Size (ID)	10mm (3/8")	12mm (1/2")	12mm (1/2")
Hose Length	20m	15m	20m
Hose Material	Premium Reinforced PVC	Premium Reinforced PVC	Premium Reinforced PVC
Working Pressure	275 psi	275 psi	275 psi
Max Temperature	60°C (140°F)	60°C (140°F)	60°C (140°F)
Reel Inlet	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)
Hose Outlet	1/4" BSP (M)	3/8" BSP (M)	3/8" BSP (M)
Other Available Colour:	Standard	AR320B-01	AR415B-01
	RACR	ARC320B-01	ARC415B-01
	Colour	Blue	Blue

Recommended to be used with:



Retracta R3 Series

COMPRESSED AIR/WATER

The Retracta R3 – Standard AW reel is the most common hose combination in workshops. With air and water compatibility, the AW is encased in the industrial strength poly reel and is ideal for most entry-level conditions.

10
YEARS
MACNAUGHT
WARRANTY™



Why choose this product?

The robust Retracta R3 - AW series reels have the ability to carry both compressed air & water.

Features & Benefits

- Highly durable Premium Reinforced PVC hose
- Upgraded main spring made with TRC – Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable

Applications:

Suitable for use across all industries

Service Parts available when requested.

Retracta R3 Series


COMPRESSED AIR/WATER

10
YEARS
MACNAUGHT
WARRANTY™



Standard	AW315B-01	AW320B-01	AW415B-01	AW420B-01
Case Colour	Blue	Blue	Blue	Blue
Hose Size (ID)	10mm (3/8")	10mm (3/8")	12mm (1/2")	12mm (1/2")
Hose Length	15m	20m	15m	20m
Hose Material	Reinforced PVC	Reinforced PVC	Reinforced PVC	Reinforced PVC
Working Pressure	250 psi	250 psi	250 psi	250 psi
Max Temperature	60°C (140°F)	60°C (140°F)	60°C (140°F)	60°C (140°F)
Reel Inlet	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)	3/8" BSP (F)
Hose Outlet	1/4" BSP (M)	1/4" BSP (M)	3/8" BSP (M)	3/8" BSP (M)

Recommended to be used with:



BB200 R3 Bench Mount Bracket

RA-AGA Aluminum Air Blow Gun Kit

RA-AGP 100mm Adjustable Flow Air Bow Gun

Retracta R3 Series

WATER - HOT WASH



Unique patented RACR (on selected models)

Working pressure
290psi at 20°C
100psi at 80°C

Available in
15m and 20m variants



High Temperature resistant PVC hose rated to 85°C

1/2" (12mm) ID hose

Easy to clean hose cover

Why choose this product?

The Retracta R3 Hot Wash reel is extremely reliable for hot water applications up to 85°C and 290psi. Ideal for use in food manufacturing and preparation, bars, clubs and service centres.

Features & Benefits


- Hose applicable for use with hot water up to temperatures of 85°C
- High temp resistant PVC with pressure rating to 290psi at 20°C
- Fully serviceable
- RACR* - on selected models

Applications:

Cleaning food processing area and equipment in meat, poultry, confectionery and dairy. Hot water wash down areas including bars, clubs, commercial kitchen and service centre

Service Parts available when requested.

Recommended to be used with:



WATER - COLD WATER



Unique patented RACR (on selected models)

Working pressure
150psi

Available in 20m



1/2" (12mm) ID hose

Flexible & abrasive resistant hose cover

Premium Reinforced PVC hose

Includes spray nozzle

Why choose this product?

The Retracta R3 Cold Water reel is suited for industrial applications requiring high pressure water delivery via brass snap-on fitting.

Features & Benefits


- Premium reinforced PVC hose pressure rated to 150psi
- Brass hose connector
- Fully serviceable
- RACR* - on selected models

Applications:

Food and industrial wash down application. Outdoor, Garden and Horticultural

Service Parts available when requested.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

Standard	CW420B-01
RACR*	CWC420B-01
Case Colour	Blue
Hose Size (ID)	12mm (1/2")
Hose Length	20m (65ft)
Hose Material	Premium reinforced PVC
Working Pressure	150psi
Max Temp.	60°C (140°F)
Reel Inlet	1/2" BSP (F)
Hose Outlet	Brass hose connector

Standard	HW415R-01	HW420R-01
RACR*	HWC415R-01	HWC420R-01
Case Colour	Red	Red
Hose Size (ID)	12mm (1/2")	12mm (1/2")
Hose Length	15m (50ft)	20m (65ft)
Hose Material	High Temp. Chemical Resistant PVC	
Working Pressure	290psi at 20°C 100psi at 80°C	
Max Temperature	85°C (185°F)	85°C (185°F)
Reel Inlet	1/2" BSP (F)	1/2" BSP (F)
Hose Outlet	1/2" BSP (M)	1/2" BSP (M)

Retracta R3 Series

WATER - HIGH PRESSURE



The Retracta R3 – High Pressure Hot wash reel is coupled with a steel wire braided rubber hose and industrial strength hose reel case ensuring complete confidence in high pressure water delivery.



Why choose this product?

The Retracta R3 High Pressure reel is the ultimate in high pressure water delivery. Rated to pressures up 3000psi and temperatures up to 95°C this reel and hose combination also delivers confidence in most water applications.

Features & Benefits

- Hose applicable for high pressure applications up to 3,000psi
- Rated to water temperatures up to 95°C
- Fully serviceable
- RACR® - on selected models

Applications:

Outdoor high pressure cleaning, industrial cleaning, car wash

Service Parts available when requested.

Recommended to be used with:




BB200 R3 Bench Mount Bracket

WATER - GARDEN/HORTICULTURE



The Retracta R3 – Garden/Horticulture reel is available in 2 different reel case colours and come standard with the innovative RetractaFLEX hybrid polymer hose.



Why choose this product?

The Retracta R3 Garden/Horticulture looks as good as it works in garden and horticultural applications. Available in 2 different colours, the innovative RetractaFLEX hose comes standard.

Features & Benefits

- Hybrid polymer hose to prevent hose tangles and kinking.
- High wear resistance mouth with ProGlide
- Fully serviceable

Standard	DR418G-03	DR425G-03	DR418P-03	DR425P-03	DR418D-03	DR425D-03
Case Colour	Green	Green	Beige	Beige	Dark Grey	Dark Grey
Hose Size (ID)	12mm (1/2")	12mm (1/2")	12mm (1/2")	12mm (1/2")	12mm (1/2")	12mm (1/2")
Hose Length	18m	25m	18m	25m	18m	25m
Hose Color	Green	Green	Green	Green	Green	Green
Hose Material	RetractaFLEX Hybrid Polymer					
Working Pressure	150 psi	150psi	150 psi	150psi	150 psi	150 psi
Max Temperature	60°C (140°F)					
Reel Inlet	Hose & Tap Connector					
Hose Outlet	Hose Connector	Hose Connector	Hose Connector	Hose Connector	Hose Connector	Hose Connector

Applications:

Domestic outdoor, garden and horticultural.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

Service Parts available when requested.

Retracta R3 Series

OIL

The Retracta R3 Oil reels are supplied with two different lengths of hoses supported by a dark grey or blue reel. The R3 Premium can be upgraded with the RACR system offering true control by allowing the user to set the speed of return to suit their individual requirements.



Unique patented RACR (on selected models)

Working pressure 1,000psi

Premium SAE Wire Reinforced Rubber Hose



Available in 1/2" (12mm) hose sizes

Abrasive resistant smooth hose cover

Fully Serviceable

Standard	OMP415B-01
RACR®	OMPC415B-01
Case Colour	Blue
Hose Size (ID)	12mm (1/2")
Hose Length	15m
Hose Material	Wire Reinforced Rubber (SAE100R17)
Working Pressure	1000 psi
Max Temperature	90°C (194°F)
Reel Inlet	1/2" BSP (F)
Hose Outlet	1/2" BSP (M)

Features & Benefits

- Highly durable Double Reinforced Rubber (R3 Premium) or Steel Wire Braided Rubber
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Why choose this product?

The R3 oil reels are ideal choice for peace of mind reliability and performance.

Applications:

Suitable for use across all industries

Service Parts available when requested.

Recommended to be used with:



Retracta R3 Series

GREASE


The Retracta R3 Grease reels are supplied with 2 different lengths of hoses supported by a black or blue reel. The R3 Premium can be upgraded with the RACR system offering true control by allowing the user to set the speed of return to suit their individual requirements.



Unique patented RACR (on selected models)

Working pressure 5,000psi

Premium SAE Wire Reinforced Rubber Hose



Available in 1/4" (6mm) hose sizes

Abrasive resistant hose cover

Fully Serviceable

Standard	GR215K-01	GR210B-01
RACR®	GRC215K-01	X
Case Colour	Black	Blue
Hose Size (ID)	6mm (1/4")	6mm (1/4")
Hose Length	15m	10m
Hose Material	Wire Reinforced Rubber (SAE100R2)	Wire Reinforced Rubber (SAE100R2)
Working Pressure	5000 psi	5000 psi
Max Temperature	100°C (212°F)	100°C (212°F)
Reel Inlet	1/4" BSP (F)	1/4" BSP (F)
Hose Outlet	1/4" BSP (M)	1/4" BSP (M)

Why choose this product?

The R3 grease reels are ideal choice for peace of mind reliability and performance.

Applications:

Suitable for use across all industries

Features & Benefits

- Highly durable Double Reinforced Rubber (R3 Premium) or Steel Wire Braided Rubber
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Service Parts available when requested.

Recommended to be used with:



Retracta R3 Series


WELDING GAS - OXY/ACET

The Retracta R3 Oxy/Acetylene reel is supplied with twin gas hose, made from reinforced rubber compliant to AS 1335 to ensure outstanding support in the welding environment. RACR version also available.



WELDING GAS - OXY/LPG

The Retracta R3 Oxy/LPG reel is supplied with twin gas hose, made from reinforced rubber compliant to AS 1335 to ensure outstanding support in the welding environment. RACR version also available.



Why choose this product?

Built for peace of mind reliability, performance and safety

Standard	OA215B-04
RACR®	OAC215B-04
Case Colour	Blue
Hose Size (ID)	Twin 5mm (3/16")
Hose Length	15m
Hose Material	Reinforced Rubber (AS1335)
Working Pressure	175 psi
Max Temperature	80°C (176°F)
Reel Inlet	Gas Thread UNF (M)
Hose Outlet	Gas Thread UNF (F)

Features & Benefits

- Highly durable Double Reinforced Rubber
- Upgraded main spring made with TRC – Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® – on selected models

Applications:

Suitable for use in all industries where Oxy /Acetylene is required

Service Parts available when requested.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

Why choose this product?

Built for peace of mind reliability, performance and safety

Standard	OG215K-04
RACR®	OGC215K-04
Case Colour	Black
Hose Size (ID)	Twin 5mm (3/16")
Hose Length	15m
Hose Material	Reinforced Rubber (AS1335)
Working Pressure	175 psi
Max Temp.	60°C (140°F)
Reel Inlet	Gas Thread UNF (M)
Hose Outlet	Gas Thread UNF (F)

Features & Benefits

- Highly durable Double Reinforced Rubber
- Upgraded main spring made with TRC – Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® – on selected models

Applications:

Suitable for use in all industries where Oxy /LPG is required

Service Parts available when requested.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

Retracta R3 Series

WELDING GAS - ARGON



The Retracta R3 Argon reel is supplied with a 20 metre hose, made from reinforced rubber compliant to AS 1335 to ensure outstanding support in the welding environment specifically to handle Argon. RACR version also available.



Why choose this product?

The R3 Argon gas reel can be used in all applications for arc welding such as gas metal arc welding and gas tungsten arc welding.

Features & Benefits

- Highly durable Double Reinforced Rubber
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Applications:

Service Bays / Garages, Manufacturing / Fabrication Shops, Construction, Welding Carts, Shipyards, Transport Service.

Service Parts available when requested.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

WELDING GAS - LPG



The Retracta R3 LPG reel is supplied with a 20 metre hose, made from reinforced rubber compliant to AS 1335 to ensure outstanding support in the welding environment specifically to handle LPG. RACR version also available.



Why choose this product?

The R3 LPG gas reel has been created for the delivery and transfer of propane gas in commercial & industrial applications encased in a Retracta R3 reel.

Features & Benefits

- Highly durable Double Reinforced Rubber
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Applications:

Service Bays / Garages, Manufacturing / Fabrication Shops, Construction, Welding Carts, Shipyards, Transport Service.

Service Parts available when requested.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

Standard	ARG220D-04
RACR®	ARGC220D-04
Case Colour	Dark Grey
Hose Size (ID)	5mm (3/16")
Hose Length	20m
Hose Material	Reinforced Rubber (AS1335)
Working Pressure	200 psi
Max Temperature	60°C
Reel Inlet	Gas Thread UNF (M)
Hose Outlet	Gas Thread UNF (F)

Standard	LPG220K-04
RACR®	LPGC220K-04
Case Colour	Black
Hose Size (ID)	5mm (3/16")
Hose Length	20m
Hose Material	Reinforced Rubber (AS1335)
Working Pressure	200 psi
Max Temperature	60°C
Reel Inlet	Gas Thread UNF (M)
Hose Outlet	Gas Thread UNF (F)

Retracta R3 Series


CHEMICAL - WEEDICIDE / PESTICIDE

The Retracta R3 Weedicide/Pesticide reel is supplied with a 16 metre chemical resistant PVC hose designed specifically to handle, transfer and dispense weedicide, pesticide and chemical. RACR version also available.



Unique patented RACR (on selected models)

Working Pressure: 250 psi



Why choose this product?

The R3 Weedicide/Pesticide hose reel has been created for the delivery and transfer of weedicide, pesticide and general chemicals.

Standard	WD316R-01
RACR	WDC316R-01
Case Colour	Red
Hose Size (ID)	10mm (3/8")
Hose Length	16m
Hose Material	Chemical Resistant PVC
Working Pressure	250 psi
Max Temperature	60°C (140°F)
Reel Inlet	3/8" BSP (F)
Hose Outlet	1/4" BSP (M)

Features & Benefits

- Highly durable Chemical resistant PVC
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Applications:

Farming, Horticulture, Chemical plant and Outdoor

Service Parts available when requested.

Recommended to be used with:



BB200 R3 Bench Mount Bracket

F.R.A.S. AIR / WATER REEL


The Retracta R3 FRAS reel is supplied with a 15 metre reinforced PVC hose, featuring fire resistant anti-static property to meet the mining specific application. Reel constructed in polypropylene and brass, no aluminium.



Equipped with Fire Resistant Anti Static Hose

Working Pressure: 300 psi

Abrasive resistant hose cover



*Fire Resistant Anti Static only applicable to hose, not including reel body

Why choose this product?

The Retracta FRAS reel features hose made with fire resistant material and a conductive outer strip connected to its conductive inner wall. Combine with our durable Retracta R3, it ideal for harsh mining environment.

Standard	FRAS415D-01
Case Colour	Dark Grey
Hose Size (ID)	12mm (1/2")
Hose Length	15m
Hose Material	Reinforced PVC (F.R.A.S)
Working Pressure	300 psi
Max Temperature	60°C (140°F)
Reel Inlet	1/2" BSP (F)
Hose Outlet	1/2" BSP (M)

Features & Benefits

- Highly durable reinforced PVC (F.R.A.S)
- Upgraded main spring made with TRC - Texture Rolled Carbon
- Safe tensioning mechanism
- High wear resistance mouth with ProGlide
- Fully serviceable
- RACR® - on selected models

Applications:

Food processing and food preparation. Hot water wash down areas including bars, clubs and service centres.

Service Parts available when requested

Recommended to be used with:



BB200 R3 Bench Mount Bracket

ACCESSORIES

The Retractable range has now expanded to include sleek new accessories specially designed for our iconic Retractable poly Hose Reels. From new Air Blow Guns, to new fittings and nozzles, all Retractable accessories have been made to compliment our hose reels.



Aluminum Air Blow Gun Kit
RA-AGA

Features & Benefits


- Light weight and durable aluminium body
- ¼" Nitto style fitting included
- 3 Nozzles included for versatile application
- Compact ergonomic handle design



100mm Adjustable Flow Air Blow Gun
RA-AGP

Features & Benefits

- ¼" Nitto style fitting included
- Adjustable flow control
- Ergonomic handle design
- Steel insert thread connection
- Durable nylon body for impact and wear resistant



R3 Multi Position Locking Bracket
RA-MLB

Features & Benefits

- Hold and lock hose reel at desired angle and direction
- Simple setup and easy to adjust
- Compatible to existing Retractable R3 hose reels



Heavy Duty Hot Water Trigger Nozzle
RA-HGB

Features & Benefits

- Adjustable spray pattern by trigger (conical/pencil)
- Swivel inlet
- Ergonomic design
- Lightweight plastic construction
- Heavy duty Shock proof rubber ring



Hot Water Trigger Nozzle
RA-HGP

Features & Benefits

- Adjustable spray pattern by trigger (conical/pencil)
- Swivel inlet
- Ergonomic design
- Lightweight construction with trigger guard
- Shock proof protective rubber ring



Brass Water Spray Nozzle
RA-CNB

Features & Benefits

- Spray adjusts from mist to powerful jet
- Robust brass construction with a soft rubber grip



Coolant / Water Bib Dispenser Valve
RA-CBM

Features & Benefits

- Curved rubber tip for ease of dispensing
- Coolant / Water bib
- Coolant / Water faucet
- Radiator bib

Part Number	Description
AIR BLOW GUN	
RA-AGA *	Aluminium Air Blow Gun Kit
RA-AGP *	100mm Adjustable Flow Air Blow Gun
WATER NOZZLES	
RA-CNB	Brass Water Spray Nozzlev
RA-HGB	Heavy Duty Hot Watter Trigger Nozzle
RA-HGP	Hot Watter Trigger Nozzle
RA-CBM	Coolant / Water Bib Dispenser Valve
LOCKING BRACKET	
RA-MLB	R3 Multi Position Locking Bracket

RETRACTAFLEX AIR HOSE



For a light weight and easy to handle air hose, try out our RetractableFLEX Air Hose. This hybrid polymer high flex hose is kink-free under pressure and features a HI-VIS orange colour for workplace safety.



Part Number	Description
RETRACTAFLEX AIR HOSE	
AH1010	3/8" x 10m with Nitto Style Coupler
AH1020	3/8" x 20m with Nitto Style Coupler
AH1030	3/8" x 30m with Nitto Style Coupler
AH1210	1/2" x 10m with Nitto Style Coupler
AH1220	1/2" x 20m with Nitto Style Coupler
AH1230	1/2" x 30m with Nitto Style Coupler

RetractableFLEX AIR HOSE

Features & Benefits

- Hybrid polymer high flex hose
- Kink-free under pressure
- Memory free hose, lays flat on the floor
- Light weight and easy to handle
- Nitto style 1 touch quick release fittings



Part Number	Description
NITTO STYLE AIR FITTING	
RA-20PM	¼" Nitto Style Plug ¼" Bsp Male Air Fitting
RA-20PF	¼" Nitto Style Plug ¼" Bsp Female Air Fitting
RA-20SM	¼" Nitto Style Socket ¼" Bsp Male Air Fitting
RA-20SF	¼" Bsp Female Fitting to Nitto Socket
RA-30SF	3/8" Bsp Female Fitting to Nitto Socket
RA-30SH30PH	Nitto Style Air Fitting Set for 3/8" Hose
RA-40SH40PH	Nitto Style Air Fitting Set for 1/2" Hose

Nitto Style Air Fitting

Features & Benefits

- Compatible with genuine Nitto couplings air tool fitting
- Corrosion resistant with Chrome plated steel
- Maximum working pressure up to 215 psi (15 bar)

MP131